



F.i. Diamond is a Polymer Modified, Fibre Reinforced Hydraulic Tile Adhesive with Hi-Tack and Non-Sag properties. Use up to 15mm thick, for the fixing of Ceramic & Porcelain Tile to the demand of External and Immersed applications. Ideal for heated slabs and large format tiles.

For bonding of Dimensionally Stable Natural Stone, Fully Vitrified, Ceramic & Porcelain Tile to:

- Concrete
- Cement Screed & Render
- Concrete Block & Brick Masonry
- Fibre Cement Sheet
- Gypsum Plaster Board
- Compatible Waterproof Membranes

Technical Performance: C2 S1 T E

Mixing:

1. Add 20 kilograms of powder to approximately 4.6-5.4 litres of water
2. Stir at 600 rpm for 2 minutes
3. Slake for 2 minutes
4. Restir for 1 minute

Approximate Coverage:

6.5 – 7.5 m² with a 6mm x 6mm notch trowel
4.0 – 5.0 m² with a 10mm x 10mm notch trowel
3.5 – 4.5 m² with a 12mm x 12mm notch trowel

Preparation:

Substrate must be solid, clean, free from dirt, dust, oils, laitance, and any release or curing agents.

Installation and Movement joints:

Installation shall be in accordance with Australian Standard **AS3958.1** and all other local building laws.

Grouting:

Grouting can commence after 24 hours at 22 degrees C and a relative humidity of 50%

Cleaning:

Fresh product can be cleaned with potable water.

Warranty:

Contact Fliese Imports for latest warranty information.

Contact:

Fliese Imports Pty Ltd

info@flieseimports.com.au

0447 402 462