F.i. VAPOUR BARRIER is a waterborne 2-part epoxy coating specifically designed as a single coat construction primer and a dual coat negative hydrostatic membrane for use prior to the installation of waterproofing membranes, self-leveling underlayments and tile and stone installation materials.

Suitable for over:

- Concrete
- Cement Composite Board
- Cement Masonry
- Tile

Technical Performance: ASTM 7088; WVT 1.33gm/m2/24hour; Permeance 0.0013 µg/N.s

Colour: Light Grey

Approximate Coverage: 15litre Part A + 15Litre Part B = 90m2 single coat / 45m2 dual coat

Preparation: Substrate must be structurally sound, solid, clean, free from dirt, dust, oils, laitance, and any release or curing agents. Ambient and surface temperature to be between 8°C and 32°C.

Mixing: Stir individual components prior in case of settling, Mix 1 Part A to 1 Part B in a clean mixing pail for 2-3 minutes with a slows speed mixer, ensure product is completely mixed. Pot life of approximately 2 hours.

Installation: Apply each coat by paint brush or long nap paint roller, each coat must have a wet film thickness 1.5mm to achieve a dried film thickness on 0.625mm. 2 coats shall be no less than 1.25mm dry film thickness. **Note:** Single priming coats can be thinned with up to 15% potable water. This will not be considered as the first coat of a dual coat negative membrane.

Overlayments: Tiling and waterproof membrane installation can commence after 24 hours at 22 degrees C and a relative humidity of 50%.

Cleaning: Fresh product can be cleaned with potable water.

Limitations:

- Not for use as a positive waterproofing membrane
- Overlayments must be installed within 5 days
- Not stable to ultraviolet light
- Not to be used as a trafficable finish
- Not for installation on substrates below 8°C and above 32°C
- Not to be used when humidity is above 90%
- Not for covering or bridging over cold, construction, control or expansion joints.
- Not for preventing moisture over existing cracks or new cracks that develop after installation
- Contact Fliese Imports for any Technical Service

Warranty: Contact Fliese Imports for latest warranty information.

Contact: Fliese Imports Pty Ltd info@flieseimports.com.au 0447 402 462